TOSHIBA HALL SENSOR GaAs ION IMPLANTED PLANAR TYPE

THS125

HIGH STABILITY MOTOR CONTROL. DIGITAL TACHOMETER.

CRANK SHAFT POSITION SENSOR.

- Super Small Package.
- Excellent Temperature Characteristics.
- Wide Operating Temperature Range. (; −55~125°C)
- Excellent Output Voltage Linearity.
- High Internal Resistance. : R_d = 1000Ω (Min.)
- Low Residual Voltage Ratio. : V_{HO}/V_H = ±5% (Max.)

Unit in mm



1(+)−3(−) (INPUT)
2(+)−4(−) (OUTPUT)

JEDEC	—
EIAJ	—
TOSHIBA	10-2A1A

Weight : 0.0047g

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Control Voltage	V_C	12**	V
Power Dissipation	P_D	150**	mW
Operating Temperature Range	T_{opr}	−55~125	°C
Storage Temperature Range	T_{stg}	−55~150	°C

** Mounted on a printed circuit board.

Marking



ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Internal Resistance (Input)	R_d	I_C = 1mA	1000	1250	1500	Ω
Residual Voltage Ratio	V_{HO}/V_H	V_C = 5V, B = 0 / B = 0.1T	—	—	±5	%
Hall Voltage (Note 1)	V_H	V_C = 5V, B = 0.1T	130	150	170	mV
Temperature Coefficient (Note 2)	V_{HT}	I_C = 5mA, B = 0.1T T1 = 25°C, T2 = 125°C	—	—	−0.06	% / °C
Linearity (Note 3)	ΔK_H	V_C = 5V, B1 = 0.05T, B2 = 0.1T	—	—	2	%
Specific Sensitivity (Note 4)	K*	V_C = 5V, B = 0.1T	—	30	—	$\times 10^{-2}$ / T
Internal Resistance (Output)	R_{OUT}	I_C = 1mA	1800	2375	3000	Ω

Note 1 : $V_H = V_{HM} - V_{HO}$ (V_{HM} is meter indication)

Note 2 : $V_{HT} = \dfrac{1}{V_{H(T1)}} \cdot \dfrac{V_{H(T2)} - V_{H(T1)}}{T2 - T1} \times 100\ (\% / °C)$ V_{HO} : Residual Voltage

Note 3 : $\Delta K_H = \dfrac{K_{H(B2)} - K_{H(B1)}}{1/2\{K_{H(B1)} + K_{H(B2)}\}} \times 100\ (\%)$, $K_H = \dfrac{V_H}{I_C \cdot B}$ K_H : Product Sensitivity

Note 4 : $K^* = V_H / (R_d \times I_C \times B) = K_H / R_d$

961001EAA2


VH – VC
B=0.1T
Ta=25°C
HALL VOLTAGE VH (mV)
CONTROL VOLTAGE VC (V)


VH – B
VC=5V
Ta=25°C
HALL VOLTAGE VH (mV)
MAGNETIC FLUX B (T)


Rd – Ta
IC=1mA
INTERNAL RESISTANCE (INPUT) Rd (Ω)
AMBIENT TEMPERATURE Ta (°C)


ROUT – Ta
IC=1mA
INTERNAL RESISTANCE (OUTPUT) ROUT (Ω)
AMBIENT TEMPERATURE Ta (°C)


VH – Ta
(CONSTANT VOLTAGE OPERATION)
VC=5V
B=0.1T
HALL VOLTAGE VH (mV)
AMBIENT TEMPERATURE Ta (°C)